



Loudspeakers Series

TM352 - 450w 15 inch / 2 inch Multi-application

The Pulse **TM352** and **TM12** are, by design, made to be the single most useful speaker you've ever owned.

A unique cabinet shape makes them a natural for use as a wedge monitor, yet the overall design, with recessed handles and recessed input jackplate means the cabinet can be easily used vertically as a front of house loudspeaker. An overall trapezoidal shape and integrated standmount adapter means the Pulse TM-Series monitors can be pole mounted for front of house use, or arrayed in any install.

Features

- 450 Watt Power Handling
- Unique Multi-application Cabinet Design
- 15-inch Speaker and 2-inch High Frequency Driver with Tweeter
- 50 x 60 degree horn dispersion
- PTC™ Component Protection
- Recessed Standmount Adaptor and Handles
- 1/4-inch Phone and Speakon™ Inputs

TM352 - Black Ultrathane (Painted) Finish

TM352C - Black Ozite (Carpet) Finish

Specifications

System Type	Three-Way
Active or Passive	Passive
Program Power (Watts)	450
Biampable	Yes
Nominal Impedance (Ohms)	8
Sensitivity (dB @1Watt/1m)	100
Max SPL (dB)	127
Frequency Response (Hz +/- 3db)	60 - 18k
Crossover Frequency (Hz)	1800 / 10k
Driver Configuration	15 inch / 2 inch / Tweeter
HF Driver(s)	2.5 inch Titanium / Piezo Tweeter
HF Horn	ABS Waveguide
HF Dispersion (°H x °V)	50 x 60
HF Protection	PTC
LF Driver(s)	15 inch
Inputs - 1/4" Jacks	2
Inputs - Speakon 4-pin	2
Bar Handles	2
Pole Mount Adapter (1 3/8"-3.5cm)	1
Enclosure Materials	15mm (5/8inch) 11-ply Russian Birch
Grille	Perforated Metal
Covering / Finish	Black Ultrathane Paint
Optional Covering / Finishes	Black Ozite Carpet (TM352C)
Dimensions (DWH xbackW, inches)	10 x 18 x 29
Dimensions (DWH xbackW, cm)	25 x 45 x 74
Weight (lbs/kg)	66 / 30
*	Specifications subject to change without notice